

**2 LEGS SLING
WIRE ROPE**



Main characteristic:

Sling wire rope single leg, galvanized or ungalvanized rope with soft eyes or heavy stub-end galvanized thimbles on ends spliced by talurit clamps Acc. to EN 13411

Safety factor:

MBL equals 5xSWL

Certificates:

- "EC" declaration of conformity acc. to EN 13414-1
- Italmat can be supplied, upon request, third parties test certificate with IACS member such RINA - LLOYD'S REGISTER OF SHIPPING - BUREAU VERITAS - DNV - others

**BRACHE IN FUNE
ACCIAIO A 2 TRATTI**

Caratteristiche generali:

Tiranti in fune acciaio lucido o zincato con asole o radance ad ogni estremità impiombate con manicotti pressati talurit a norma EN 13411

Coefficiente di sicurezza:

CMU 1:5 Carico di rottura

Certificazione:

- Certif. di conformità "CE" a norma EN 13414-1
- Italmat può fornire a richiesta certificazione con Ente di Classifica IACS quali RINA - LLOYD'S REGISTER OF SHIPPING - BUREAU VERITAS - DNV - altri

T2TR

2 tratti con radance
2 legs with thimbles

T2TS

2 tratti con grilli
2 legs with shackles

T2TG

2 tratti con ganci con
linguetta di sicurezza
2 legs with hook with
safety latch

T2TP

2 tratti con pinza per
sollevamento
2 legs with lifting clamp

