

## GANCIO PER BRACHE EGK/GK - EGKN/GKN



**Materiale:** Acciaio ad elevata resistenza Ni Cr MO T8 - Grado 80

**Coefficiente di sicurezza:**  
CMU 1:4 Carico di rottura

**Finitura:** Verniciatura colorata antiruggine

### Certificazione:

- Certificato di conformità "CE"
- Italmet può fornire a richiesta certificazione con Ente di Classifica IACS quali RINA - LLOYD'S REGISTER OF SHIPPING - BUREAU VERITAS - DNV - altri



## SLING HOOK EGK/GK - EGKN/GKN

**Material:** High tensile grade steel Ni Cr Mo T8 - Grade 80

**Safety Factor:**  
WLL 1:4 Breaking force

**Finish:**  
Painted Rustproof

### Certificates:

- "EC" Declaration of conformity
- Italmet can be supplied, upon request, third parties test certificate with IACS members such RINA - LLOYD'S REGISTER OF SHIPPING - BUREAU VERITAS - DNV - others



Codice senza sicura	Codice con sicura	CMU* WLL*	Catena di riferimento	Dimensioni Main dimension				Peso Weight
Code without latch	Code with latch	kg	mm	L mm	B mm	G mm	H mm	kg
GGEGK/GK-7/8-8	GGEGKN/GKN-7/8-8	2000	7/8	95	33	17	22	0,5
GGEGK/GK-10-8	GGEGKN/GKN-10-8	3200	10	121	40	20	29	0,9
GGEGK/GK-13-8	GGEGKN/GKN-13-8	5400	13	147	48	27	36	1,9
GGEGK-GK-16-8	GGEGKN/GKN-16-8	8000	16	170	56	34	44	3,4
GGEGK/GK-19/20-8	GGEGKN/GKN-19/20-8	12500	19	212	73	43	51	5,8

\* Il carico di lavoro (CMU) è inteso con un tiro verticale

\* The Work Load Limit (WLL) is for vertical line pull application

## GANCIO PER FONDERIA OKE



**Materiale:** Acciaio ad elevata resistenza Ni Cr MO T8 - Grado 80

**Coefficiente di sicurezza:**  
CMU 1:4 Carico di rottura

**Finitura:** Verniciatura colorata antiruggine

### Certificazione:

- Certificato di conformità "CE"
- Italmet può fornire a richiesta certificazione con Ente di Classifica IACS quali RINA - LLOYD'S REGISTER OF SHIPPING - BUREAU VERITAS - DNV - altri



## FOUNDRY HOOK OKE


**Material:** High tensile grade steel Ni Cr Mo T8 - Grade 80

**Safety Factor:**  
WLL 1:4 Breaking force

**Finish:**  
Painted Rustproof

### Certificates:

- "EC" Declaration of conformity
- Italmet can be supplied, upon request, third parties test certificate with IACS members such RINA - LLOYD'S REGISTER OF SHIPPING - BUREAU VERITAS - DNV - others



Codice	CMU* WLL*	Catena di riferimento	Dimensioni Main dimension						Peso Weight
Code	kg	mm	L mm	B mm	E mm	F mm	G mm	H mm	kg
GGOKE-7/8-8	2000	7,8	122	63	25	11	18	26	0,6
GGOKE-10-8	3200	10	150	76	32	14	25	30	1,2
GGOKE-13-8	5400	13	182	90	40	18	32	38	2,3
GGOKE-16-8	8000	16	215	102	50	22	40	45	3,9
GGOKE-18/20-8	12500	19	247	114	60	26	46	57	6,1
GGOKE-26-8	21600	26	300	113	66	38	64	73	16,4
GGOKE-32-8	32000	32	384	145	80	48	77	94	35

\* Il carico di lavoro (CMU) è inteso con un tiro verticale

\* The Work Load Limit (WLL) is for vertical line pull application