

SNATCH BLOCK FOR STEEL WIRE ROPE USE UNAV 4478



PASTECHE APRIBILE PER FUNI METALLICHE UNAV 4478

Material:

- Pulley: Cast iron G22 UNI 668
- Ear-ring: Bronze

Finish:

Galvanized

Certificates:

- "EC" declaration of conformity
- Certificate 3.1.B. in acc. to EN 10204 on request
- Italmat can be supplied, upon request, third parties test certificate with IACS member such RINA - LLOYD'S REGISTER OF SHIPPING - BUREAU VERITAS - DNV - others



Materiale:

- Puleggia: Ghisa G22 UNI 668
- Boccola: Bronzo

Finitura:

Zincato

Certificazione:

- Certificato di conformità "CE"
 - Certif. 3.1.B. a norma EN 10204 su richiesta
- Italmat può fornire a richiesta certificazione con Ente di Classifica IACS quali RINA - LLOYD'S REGISTER OF SHIPPING - BUREAU VERITAS - DNV - altri

Codice Code	Ø fune Ø rope mm	CMU / WLL		L mm	A mm	Ø Puleggia Ø Pulley t	Peso Weight kg
		Linea di tiro Line pull t	Sospendita Eye pull t				
4478.0100	11	1	2	330	145	135	11
4478.0200	15	2	3,9	450	196	185	14
4478.0315	19	3,15	6,2	540	232	220	25
4478.0500	24	5	9,8	690	304	290	49
4478.0800	30	8	15,6	860	380	365	85
4478.1000	34	10	19,6	965	428	410	113
4478.1250	38	12,5	24,5	1070	475	456	167

SNATCH BLOCK FOR SYNTETHICS ROPE USE UNAV 4536



PASTECHE APRIBILE PER FUNI TESSILI UNAV 4536

Material:

- Pulley: Cast iron G22 UNI 668
- Ear-ring: Bronze

Finish:

Galvanized

Certificates:

- "EC" declaration of conformity
- Certificate 3.1.B. in acc. to EN 10204 on request
- Italmat can be supplied, upon request, third parties test certificate with IACS member such RINA - LLOYD'S REGISTER OF SHIPPING - BUREAU VERITAS - DNV - others



Materiale:

- Puleggia: Ghisa G22 UNI 668
- Boccola: Bronzo

Finitura:

Zincato

Certificazione:

- Certificato di conformità "CE"
 - Certif. 3.1.B. a norma EN 10204 su richiesta
- Italmat può fornire a richiesta certificazione con Ente di Classifica IACS quali RINA - LLOYD'S REGISTER OF SHIPPING - BUREAU VERITAS - DNV - altri

Codice Code	Ø fune Ø rope mm	CMU / WLL		L mm	A mm	Ø Puleggia Ø Pulley t	Peso Weight kg
		Linea di tiro Line pull t	Sospendita Eye pull t				
4536.0100	32	1	2	470	215	200	13
4536.1600	41	1,6	3,15	595	285	270	18
4536.0200	48	2	4	695	435	324	28
4536.0250	54	2,5	5	800	395	375	36

