

**SNATCH BLOCK FOR STEEL WIRE ROPE USE UNAV 4478**



**PASTECHE APRIBILE PER FUNI METALLICHE UNAV 4478**

**Material:**

- Pulley: Cast iron G22 UNI 668
- Ear-ring: Bronze

**Finish:**

Galvanized

**Certificates:**

- "EC" declaration of conformity
- Certificate 3.1.B. in acc. to EN 10204 on request
- Italmet can be supplied, upon request, third parties test certificate with IACS member such RINA - LLOYD'S REGISTER OF SHIPPING - BUREAU VERITAS - DNV - others



**Materiale:**

- Puleggia: Ghisa G22 UNI 668
- Boccola: Bronzo

**Finitura:**

Zincato

**Certificazione:**

- Certificato di conformità "CE"
  - Certif. 3.1.B. a norma EN 10204 su richiesta
- Italmet può fornire a richiesta certificazione con Ente di Classifica IACS quali RINA - LLOYD'S REGISTER OF SHIPPING - BUREAU VERITAS - DNV - altri

Codice Code	Ø fune Ø rope mm	CMU / WLL		L mm	A mm	Ø Puleggia Ø Pulley t	Peso Weight kg
		Linea di tiro Line pull t	Sospendita Eye pull t				
4478.0100	11	1	2	330	145	135	11
4478.0200	15	2	3,9	450	196	185	14
4478.0315	19	3,15	6,2	540	232	220	25
4478.0500	24	5	9,8	690	304	290	49
4478.0800	30	8	15,6	860	380	365	85
4478.1000	34	10	19,6	965	428	410	113
4478.1250	38	12,5	24,5	1070	475	456	167

**SNATCH BLOCK FOR SYNTHETICS ROPE USE UNAV 4536**



**PASTECHE APRIBILE PER FUNI TESSILI UNAV 4536**

**Material:**

- Pulley: Cast iron G22 UNI 668
- Ear-ring: Bronze

**Finish:**

Galvanized

**Certificates:**

- "EC" declaration of conformity
- Certificate 3.1.B. in acc. to EN 10204 on request
- Italmet can be supplied, upon request, third parties test certificate with IACS member such RINA - LLOYD'S REGISTER OF SHIPPING - BUREAU VERITAS - DNV - others



**Materiale:**

- Puleggia: Ghisa G22 UNI 668
- Boccola: Bronzo

**Finitura:**

Zincato

**Certificazione:**

- Certificato di conformità "CE"
  - Certif. 3.1.B. a norma EN 10204 su richiesta
- Italmet può fornire a richiesta certificazione con Ente di Classifica IACS quali RINA - LLOYD'S REGISTER OF SHIPPING - BUREAU VERITAS - DNV - altri

Codice Code	Ø fune Ø rope mm	CMU / WLL		L mm	A mm	Ø Puleggia Ø Pulley t	Peso Weight kg
		Linea di tiro Line pull t	Sospendita Eye pull t				
4536.0100	32	1	2	470	215	200	13
4536.1600	41	1,6	3,15	595	285	270	18
4536.0200	48	2	4	695	435	324	28
4536.0250	54	2,5	5	800	395	375	36

